

Engineering Data Sheet



40170

Roxie 2 Wire Entrance Panel

- Wide angle video camera
- Surface mounted
- Audio annunciation
- LED indication of call status
- IP54 ingress protection
- IK08 shock resistance
- Built in transponder for access control
- Additional clean contact output
- System programming and configuration via Saveprog software or Vimar View wireless app or buttons on panel or Dip Switches in panel.
- Remote access control with Vimar View key app
- 1,2 or 4 call buttons (button covers ordered separately)

Brand



General Information

The Roxie 2 wire Entrance Panel is compatible with all current Vimar 2 Wire plus equipment.

The panel has LED indication of the call status and can be configured to provide audio announcements.

Proximity tokens (purchased separately if required) are programmed via the View Wireless app.

The panel can be configured to call 1, 2 or 4 devices/dwellings by specifying the number of call buttons (40171 – 1 call button, 40172 – 2 call buttons, 40174 – 4 call buttons) which are purchased separately.

Remote access can be managed via the View Key app

Additional mounting options are available which include a Rain hood and semi flush mounting frames.

Specifications

System	Vimar 2 Wire plus
Finish	Zamak with Grey RAL9007 finish
Camera	130 degree wide angle horizontal view, 82 degrees vertical view
Audio	Full duplex audio, with audio annunciation (if configured)
Lock Output	12V DC on S+ and S-, an additional clean contact output is available triggered from an additional button on the monitor.
Proximity	Built in Mifare RFID proximity reader
Mounting	Surface mount with options for Rain guard and semi flush mounting frames.
Dimensions	100mm wide x 190mm high x 32.5mm deep

Form : 04/09/24

Rev 1.0.0