Email: info@raytelsecurity.co.uk Southern Office: 01245 428510 Northern Office: 0141 582 1275

Engineering Data Sheet



Brand



General Information

This is a 316 Stainless Steel entrance panel with 3.5" colour display and tactile back illuminated keypad.

The Entrance panel is 3mm in thickness and is secured with special anti-tamper screws.

The Entrance Panel meets standard IP54 for ingress and IK08 for impact resistance. The integrated 3.5" colour display has a range of high contrast colours and a range of font sizes.

The Entrance Panel incorporates visual indicators for "Calling", "Conversation", "Lock release" and "Engaged" The Entrance Panel also includes a teleloop for T coil hearing aid users.

The Entrance Panel can be programmed to provide an address book with up to 6,400 users.

40425

Audio only Pixel Up Entrance Panel

- For Vimar Due Fili Plus
- Flush or Surface Mounting
- Anti Tamper fixings
- High impact resistance 316 Stainless Steel
- · Digital Dial backlit keypad with Braille
- Optional voice synthesis
- Teleloop as standard
- DDA Indicators
- 3.5" Colour Display Unit with customizable standby graphics.
- Stainless Steel back box.
- Surface mounting box available (Vimar ref 40440)

Specifications

| Specifications | |
|----------------|---|
| | |
| System | 2 wire due fili |
| Audio | Automatic Gain Control to optimise sound levels with echo canceller and noise reduction. Integrated Teleloop for T Coil hearing aid users |
| DDA | Graphic Icons and LED's are incorporated into the Entrance Panel to indicate "Calling" "Busy" "Conversation" and "Lock release" |
| Display | 3.5" Colour Display with 5mm polycarbonate screen protector |
| Dimensions | Front Plate 3mm x 405mm x 145mm |
| | Back Box 382mm x 124mm x 60mm |
| | |
| | |

40425 07/01/22

Rev 1.0.0