Raytel Security Systems Limited
EST. 1979 helping to keep communities safer

Email : info@raytelsecurity.co.uk
Southern Office : 01245 428510
Northern Office : 0141 582 1275

Engineering Data Sheet



40540

2 Wire Audio Handset

- **Surface Mounted**
- **Full duplex conversation with calling Entrance Panel**
- **Lock release at calling Entrance Panel**
- **Additional function button**
- **Programmable via buttons on handset, dip switches within handset or software**
- **Ringtone level slider with mute position**
- **Ringtone Volume indicator**

Brand

ELVOX
VIMAR group

General Information

The handset will provide duplex communication with the calling Entrance Panel. The call tone is generated within the handset. The handset has a dedicated button for lock release. An additional button is provided for auxiliary services which can be programmed via software.

A slider is provided to set the ringtone level, this also has a privacy (mute) position with visual indication.

An additional input is available for a Landing Call button.

An additional output is available for an external call repeater.

Specifications

System	2 Wire due fili
Controls	1 x Lock Release button. 1 x Lamp button (additional function) 1 x Ringtone level slider with indicator and mute position
Inputs	2 Wire Bus connections, Input for Landing Ringtone, output for additional ring tone.
Finish	High impact moulded plastic with high gloss white finish.
Standby Consumption	10 mA
Max Consumption	50 mA
Dimensions	95mm W x 200mm H x 28.5mm D
Termination	Screw terminals
Weight	500g
Operating Temperature	0 to +40 Degrees Centigrade

Form : 40540 **Rev 1.0.0**

E&OE. Please check critical parameters at time of order.