

## Engineering Data Sheet



# 7539/M

## 2 Wire, colour, 1 way, Door Entry Kit

### Contains:

- 1 x 7539 Tab monitor
- 1 x 13K1 Video entry panel
- 1 x 6922.1 power supply


### Main Features:

- Entrance Panel can be flush or surface mounted.
- Monitor has 3.5" LCD Colour display
- Monitor is surface mounted

### Brand

**ELVAX**

VIMAR group



### General Information

This colour video door entry kit has an attractive and modern look. It can be wired using copper Cat5e/6e cable configured to provide 2 cores.

The Tab monitor has a 3.5" colour display, glass effect finish and capacitive technology with back lit touch buttons.

The entrance Panel can be flush or surface mounted. The Entrance Panel camera unit has a 12V DC lock output integral with the system connections.

The power supply requires a switched mains connection.

### Specifications

<b>System</b>	2 wire due Fili
<b>Controls</b>	Capacitive buttons for door release, speech, self activation, auxiliary function, user control of brightness, volume and muting
<b>Monitor</b>	High impact moulded plastic with high gloss white finish.
<b>Entrance Panel</b>	Flush or surface mount, electro polished anodised aluminium.
<b>Power supply</b>	Din rail or surface mount (mains connection required)
<b>Dimensions</b>	Monitor 131mm wide, 150mm high, 26.5mm deep. Entrance Panel 168mm high, 100mm wide, surface depth 37mm, flush depth 23mm + 12mm PSU 142mm wide, 96mm high, 70mm deep

Form : 7539/M

Rev 1.0.0