

Engineering Data Sheet

7549/M

2 Wire, colour, 1 way, Door Entry Kit

Contains:


- 1 x 7549 Tab monitor
- 1 x 13K1 Video entry panel
- 1 x 6922.1 power supply

Main Features:

- Entrance Panel can be flush or surface mounted.
- Monitor has 4.3" LCD Colour display
- Monitor is surface mounted



Brand



General Information

This colour video door entry kit has an attractive and modern look. It can be wired using copper Cat5e/6e cable configured to provide 2 cores.

The Tab monitor has a 4.3" colour display, glass effect finish and capacitive technology with back lit touch buttons.

The entrance Panel can be flush or surface mounted. The Entrance Panel camera unit has a 12V DC lock output integral with the system connections.

The power supply requires a switched mains connection.

Specifications

System	2 wire due Fili
Controls	Capacitive buttons for door release, speech, self activation, auxiliary function, user control of brightness, volume and muting
Monitor	High impact moulded plastic with high gloss white finish.
Entrance Panel	Flush or surface mount, electro polished anodised aluminium.
Power supply	Din rail or surface mount (mains connection required)
Dimensions	Monitor 160mm wide, 180mm high, 45mm deep. Entrance Panel 168mm high, 100mm wide, surface depth 37mm, flush depth 23mm + 12mm PSU 142mm wide, 96mm high, 70mm deep

Form : 7549/M

Rev 1.0.0