### Email: info@raytelsecurity.com Telephone: 01245 428510

## **Engineering Data Sheet**



# IP Plug

### IP Adapter with PoE Injector

- Smart Plugs for data over mains
- Up to 1Gbps data throughput
- Built in PoE injector
- Simple 'Plug and Play' installation
- Optimised for Raytel supplied Door Entry equipment.
- Password protected plug to plug network
- FCC, CE, RoHS Certified

#### **Brand**



### **General Information**

The Raytel IP Plugs have been optimised for Door entry applications, particularly for Gate to House applications with no wiring infrastructure other than a mains connection to the gate.

Both plugs MUST be installed on the same phase of the supply.

The plugs are for indoor use only (A plug or plugs can be placed outside a dwelling as long as suitable environmental protection is provided with adequate ventilation)

Whilst the standard application for this product is two plugs providing data over mains, other combinations and permutations are possible, consult Raytel Security Systems Technical support for non-standard requirements.

### **Specifications**

System IP Plug

Maximum Distance 250m Plug to Plug

**Maximum Distance** 10m Plug to PoE equipment

Display LED Indicators
Transfer Rate (PHY) 1200Mbps
Modulation OFDM

Interface 1 x LAN10/100/100Base TX

Standard IEEE802.3at/af

**Power over Ethernet** 55V 30w / 48V 15.4w for

powered device.

**Operating Environment** Working temp 0 – 70 Deg C

Working humidity 10% - 90%

non-condensed state.

**Size** 105 x 60 x 37mm (LxWxH)

Weight 0.30kg

Form: IP Plug Rev 1.0.0