


Engineering Data Sheet

K40515.E

2 wire, colour, 1 way, video
Tab Door entry Kit 

Contains:

- 1 x 40515 Tab5SUP Video monitor
- 1 x 40151 Entrance Panel (1 button)
- 1 x 40135 Audio/Video Unit (2F+)
- 1 x 6922.1 Power supply

Main Features:

- Monitor can forward calls to mobile device when connected to local WiFi
- Entrance Panel can be flush or surface mounted.
- Monitor can be flush or surface mounted.

Brand



General Information

This colour video door entry kit has an attractive and modern look. It is recommended that the kit is wired using copper Cat5e/6e cable configured to provide 2 cores #

The Entrance Panel has an anodised aluminium finish and can be surface or flush mounted with the back boxes provided.

The 40515 Tab5SUP monitor has integrated wi-fi access to enable calls to be forwarded to a smart phone for control of the call. The monitor has configurable video voicemail, multiple ringtones, adjustable audio and video settings and the option of a system contacts list and favourites menu for quick access.



Specifications

System	2 wire due fili
Monitor	Capacitive touch keypad with backlit symbols.
Entrance Panel	Surface mounted, back lit call button with white LED's
Power supply	Din rail or surface mount (mains connection required)
Dimensions	<p>Monitor 148 mm wide, 158mm high, 24.4mm deep (surface mount) 13.1mm deep (flush mount – using 40590 box)</p> <p>Entrance Panel – Surface mount 168mm high, 100mm wide, 37mm deep.</p> <p>Entrance Panel-Flush mount 168mm high, 100mm wide, 23+12mm deep</p> <p>Power supply 96mm high, 142mm wide, 70mm deep</p>

Form : K40515.E

Rev 1.0.0