

## Engineering Data Sheet

# K40517.E

## 1 way, Tab7S UP, Two Wire Wi-Fi Door entry Kit



### Contains:

- 1 x 40517 Tab7S UP Video monitor
- 1 x 40151 Entrance Panel (1 button)
- 1 x 40135 Audio/Video Unit (2F+)
- 1 x 6922.1 Power supply

### Main Features:

- Monitor can forward calls to mobile device when connected to local Wi-Fi
- Entrance Panel can be flush or surface mounted.
- Surface mounted monitor.

### Brand




 VIMAR group

### General Information

This colour video door entry kit has an attractive and modern look. It is recommended that the kit is wired using copper Cat5e/6e cable configured to provide 2 cores #

The Entrance Panel has an anodised aluminium finish and can be surface or flush mounted with the back boxes provided.

The 40517 Tab7S UP monitor has integrated wi-fi access to enable calls to be forwarded to a smart phone via 3G/4G up to a maximum of 10 devices. The monitor has configurable video voicemail, multiple ringtones, adjustable audio and video settings and the option of a system contacts list and favourites menu for quick access.



### Specifications

<b>System</b>	2 wire due fili
<b>Monitor</b>	Capacitive touch keypad with backlit symbols.
<b>Entrance Panel</b>	Surface mounted, back lit call button with white LED's
<b>Power supply</b>	Din rail or surface mount (mains connection required)
<b>Dimensions</b>	Monitor 189 mm wide, 171mm high, 24.4mm deep (surface mount) 13.1mm deep (flush mount – using optional 40591 box) Entrance Panel – Surface mount 168mm high, 100mm wide, 37mm deep. Entrance Panel-Flush mount 168mm high, 100mm wide, 23+12mm deep Power supply 96mm high, 142mm wide, 70mm deep

Form : K40517.E

Rev 1.0.0