

Engineering Data Sheet



Brand



 **VIMAR** group

General Information

This 2 wire kit combines the stylish Roxie Entrance Panel with the 7549 monitor.

The Entrance Panel assembly has visual indicators and voice annunciation for ease of use. The entrance Panel can be configured to call 1,2 or 4 individual dwellings via simple re-configuration and a change of the button cover.

The monitor is ABS with a mirror gloss finish. The monitor has a 4.3" LCD display and touch sensitive keys. Ring tone selection, volume levels and privacy functions are incorporated into the monitor. Additional functions can be programmed via software and an interface.

K7549.R

Roxie 2 Wire Kit

Contains:

- 1 x 7549 Video monitor
- 1 x 40170 Roxie entrance Panel assembly
- 1 x 40110 Power Supply

Main Features:

- Audio annunciation at entrance panel.
- LED Indication of call status at entrance panel
- Surface mounted colour video monitor
- User selectable ring tones
- Hearing aid compatible
- Intercommunication with other devices
- Duplex voice operation

Specifications

System	Two Wire Video
Monitor	Capacitive buttons for : Door release, Self activation, 4 additional programmable buttons, User control of Brightness, volume and muting.
Entrance Panel	Surface/Semi flush mounted, back lit call button(s), IP54 ingress protection, IK08 shock resistance.
Power Supply	Din rail or surface mount (mains connection required)
Dimensions	Monitor 160mm wide, 180mm high, 45mm deep. Entrance Panel 100mm wide, 190mm high, 32.5mm deep Power supply 96mm high, 142mm wide, 70mm deep

Form : K7549R

Rev 1.0.0