

Engineering Data Sheet



Brand



General Information

This is a 7" colour monitor for use in conjunction with RSS IP Lite family of products.

Touch buttons for:

- Answer call
- Release lock

Touch icons for:

- Self Start Video from Entrance (if programmed)
- Intercommunication (if programmed)
- Call records
- Call setting (Do Not disturb, divert to mobile)
- Settings (General user settings)

Images from additional IP cameras can be displayed.

Installer/Manager modes are password protected

Internet access is required for call diversion to mobile devices. This can be provided by local user WiFi or by wired connection from the Entrance Panel to an internet connected router#

RSS IP-MW7

IP 7" Monitor with WiFi

- For use with the Raytel IP Lite family of products
- 7" Colour digital TFT display
- Resolution 800 x 480
- 1 RJ45 connector for power and data (PoE)
- White with Silver display surround
- Low profile Surface mount
- Dedicated touch buttons for speech and lock
- Video Self Start facility.
- Missed call information including snapshot of caller.
- Four user selectable favourites/short cuts
- Power / Do Not Disturb Indicator
- Intercommunication between enabled devices
- Call divert to mobile device (if enabled and appropriate internet access is available)#

Specifications

System	RSS IP Lite
Power	PoE (IEEE 802.3af Class 0)
LAN Interface	10 Base T, 100 Base TX, RJ45
Display	Full colour TFT 154 x 86 mm
Controls	Dedicated touch button for speech and lock release, all other functions via touch button on screen menus
Dimensions	161(H) x 174(W) x 22(D) mm

Form : IP-MW7

Rev 1.0.0