

Engineering Data Sheet



RSS IP-M7

IP 7" Monitor

- For use with the Raytel IP Lite family of products
- 7" Colour digital TFT display
- Resolution 800 x 480
- 1 RJ45 connector for power and data (PoE)
- White with Silver display surround
- Low profile Surface mount
- Dedicated touch buttons for speech and lock
- Video Self Start facility.
- Missed call information including snapshot of caller.
- Four user selectable favourites/short cuts
- Power / Do Not Disturb Indicator
- Intercommunication between enabled devices
- Call divert to mobile device (if enabled and appropriate internet access is available)#

Brand



General Information

This is a 7" colour monitor for use in conjunction with RSS IP Lite family of products.

Touch Icons for:

- Self Start Video
- Intercommunication (if programmed)
- Call record (missed calls, etc)
- Call Scene (Do not disturb, divert, etc)
- Settings (General user settings)

Installer/Manager modes are password protected

For a single dwelling with one or more monitors and RSS IP Entrance Panel(s) a wired connection to the dwellings private internet will be required.

For multiple dwellings a shared public, building wide wired internet connection will be required.

Specifications

System	RSS IP Lite
Power	PoE (IEEE 802.3af Class 0)
LAN Interface	10 Base T, 100 Base TX, RJ45
Display	Full colour TFT 154 x 86 mm
Controls	Dedicated touch button for speech and lock release, all other functions via touch button on screen menus
Dimensions	161(H) x 174(W) x 22(D) mm

Form : IP-M7

Rev 1.0.0