

Engineering Data Sheet



RSS IP-P1

One Button IP Door Entry Panel

- For use with the Raytel IP Lite family of products
- Surface mounting
- 1 RJ45 connector for power and data (PoE)
- Built in colour camera
- Noise cancelling audio
- Indicator for lock operation
- DDA Audio annunciations at panel
- Local connections for Lock and Exit function
- IP 65 ingress rating, IK08 impact rating

Brand



General Information

This is a single button surface mount video call door entry panel for use in conjunction with the RSS IP Lite family of products.

The entry panel can be used for single dwelling installations with multiple internal units (up to 32 monitors) calling in parallel or in larger installations where dwellings require a local door entry panel in conjunction with additional site wide entrance panels.

The single call button is illuminated and a Led is provided to indicate lock release.

Audio annunciations are made at the panel to indicate a dwelling is being called, that conversation is established and the lock is released.

Specifications

System	RSS IP Lite
Power	PoE (IEEE 802.3af Class 0)
LAN Interface	10 Base T, 100 Base TX, RJ45
Camera	170 Degree
Min illumination	5 lux
LED's	Call button and lock indicator (LED's provide diagnostic information in the event of a fault)
Finish	Brushed metal
Ingress Protection	IP65
Impact Protection	IK08
Operating Temp'	-10 to +50 Deg C
Dimensions	160(H) x 60(W) x 31.5(D) mm

Form : IP-P1

Rev 1.0.0