

Engineering Data Sheet



RSS IP-POE4 & 8 IP Network Switches

- For use with the Raytel IP Lite family of products.
- 4 or 8 FE (PoE) Ports + 2 FE Ports
- 10/100Mbps
- LED Indicators for power and data
- Switchable default VLAN and CCTV modes
- 240V Mains powered with IEC connector
- Auto learning MAC address table
- PoE Mode A 1&2 (+) 3&6 (-)
- 30W Max PoE output

Brand



General Information

This unmanaged PoE network switch is for use with the RSS IP Lite family of products.

The network switches are available with 4 or 8 PoE ports and 2 non PoE uplink ports.

The front panel incorporates LED's to indicate data and power.

A selector switch is provided on both the 4 way and the 8 way switch for additional functionality, the switch should be left in the OFF or DEFAULT positions.

Specifications

System	RSS IP Lite
POE Ports	4 or 8 dependant on model
Non POE Ports	2 (for up/down link)
Dimensions	4 Port 168(W) x 93(D) x 32mm(H) 8 Port 220(W) x 150(D) x 44mm(H)
Indication	1 x Orange Power LED 6(10) x Green Data LED's 4(8) x Orange POE Indicator
Complies with	IEEE802.3, 802.3u, 802.3af, 802.3at
Temperature Range	0 – 40 Deg C
Supply Voltage	240V AC

Form : IP-POE Switch

Rev 1.0.0